PAVEMENT TESTING AND ASSET MANAGEMENT

2023 PAPA ANNUAL CONFERENCE





ORGANIZATION

Bureau of Operations Previously a part of the Bureau of Maintenance and Operations

Asset Management Division

> Pavement Testing and Asset Management Section

> > PennDOT Annex

• Previously the BOMO Annex



PAVEMENT TESTING EQUIPMENT



ROUGHNESS (IRI) TESTING

Fleet Includes:

- 3 Highspeed Profilers
- 2 Lightweight Profilers
- 1 Walking Profiler





IRI Categories	Interstate Routes	HHS Non- Interstate Routes	Hon-NHS Routes with ADT ≥ 2000	Hon-NHS Routes with ADT < 2000	
≤ 70	Excellent	Exception			
71-75	Const	Excellent	Excellent	Econoliset	
76-100	1.0000	(and a second		CXCelleni	
101-120	F -10	Good	(Arrest		
121-150	rair	Finite	Good	Const	
151-170	Contraction of the local division of the loc	rair		Good	
171-195	-		Fair		
196-220	HOOP	Prov	the second	Fair	
> 220			Poor	Poor	







HIGHSPEED PROFILERS

- Tests are performed at traffic speeds up to 65 mph
- 3 lasers mounted in the bumper
- Two people perform this test
 - One to drive the vehicle
 - One to operate the testing equipment
- Testing occurs during the months of March - November, can vary depending on weather







LIGHTWEIGHT PROFILERS

- Tests are performed by one person both driving and operating the testing equipment
- Due to their limited size and weight, LWP's can be used within the confines of construction projects.
- Lasers also mounted on the bumper
- Monitor and operator controls located near the driver seat and computer and printer located in the back
- Testing can occur throughout the year, as long as the pavement is clear or debris and snow- colder temperatures may inaccurately reflect a rougher pavement











LIGHTWEIGHT PROGRAM

LIGHT WEIGHT PROFILING SYSTEM

Calibration Verification & Operator Certification Program Manual



DEPARTMENT OF TRANSPORTATION BUREAU OF MAINTENANCE AND OPERATIONS ASSET MANAGEMENT DIVISION ROADWAYINVENTORY AND TESTING UNIT

PUB 589 (5-21)

pennsylvania

- PTM #428, defines the method in which to measure pavement profile and determine pavement ride quality for acceptance and payment using an LWP device
- Publication 589, "Lightweight Profiling System Calibration Verification & Operator Certification Manual" outlines the program to verify calibration of all lightweights used on PennDOT jobs and the Operator Certification Process
- PennDOT wants to be assured that each individual LWP device is operated proficiently and provides accurate and precise results, and not make "blanket approvals" based on type. Because of this, a program has been developed to verify that all LWP devices are calibrated and operating properly.



LIGHTWEIGHT PROGRAM



FRICTION TESTING

Fleet Includes:

• 3 Locked-Wheel Skid Testers

Used For:

- Wet Pavement Accident Clusters
- High Friction Surface Treatment Testing
- Research Testing
- Special Request Testing





FRICTION TESTING

- Friction Testing is probably the most requested type of pavement testing.
- These devices are specially equipped pickup trucks with custom two-wheel trailers. The pickup truck is equipped with a 300 - 600gallon water tank (located in the bed), a water pump, and computer system to control the testing and record the measurements.
- Tests are performed with a two-person crew, an operator and a driver. Tests are conducted at speeds ranging between 25-50 mph when the temperature is above 32 degrees.
- To perform a test, water is sprayed immediately ahead of the trailer tire. The tire is locked and skids for a short period of time. A test cycle takes approximately 2.5 seconds. Smooth tires are usually used to create the worst-case condition.
- The computer system is used to calculate a skid number, and the data is reported to the district to determine a course of action. The higher the skid number the more friction and the lower the skid number... the less the friction.







FALLING WEIGHT DEFLECTOMETER (FWD) TESTING

Fleet Includes:

 2 Falling Weight Deflectometer Units

Used for:

- Basin Testing
- Load Transfer
- Void Detection





FALLING WEIGHT DEFLECTOMETER (FWD) TESTING

- FWDs are designed to simulate deflection of a pavement surface caused by traffic.
- FWD testing is a static test which requires traffic control. One person is needed to perform the testing.
- Tests are initiated when the operator presses a button. The sensors that are mounted on a bar are lowered onto the pavement. The FWD then drops a predetermined weight onto a load plate positioned on the pavement surface. The sensors measure the deflection of the pavement, and the computer records the measurements.
- Our FWDs are capable of testing with weights between 1,500 27,000 pounds.
- Deflection is measured in "mils," which are thousandths of an inch.
- Results are used to estimate the stiffness of the pavement.







FWD CALIBRATIONS

• Fun Fact:

The center for the North Atlantic Region is located at the PennDOT BOO Annex and has been in operation since 1992. Twenty to thirty calibrations are performed at the center annually, for State and Federal agencies, as well as private vendors, some travel from as far as North Carolina and Canada to have FWD devices calibrated at this facility. Devices are typically calibrated on an annual basis.







VIDEO LOG TESTING

Fleet Includes:

• 2 Video Log Vans

Used For:

- Video Log QA
- Warranty Projects
- Special Requests





VIDEO LOG TESTING

- PennDOT currently owns 2 video log imaging vans. Each van is equipped with lasers that are mounted in the bumper and can measure IRI.
- The video log system uses high speed cameras, custom optics and laser line projectors to acquire both 2D images and high-resolution 3D profiles of the road. It can collect data at speeds up to 65 mph.
- A ladybug camera on the roof and can collect 360-degree high resolution images. The Laser Crack Measurement System II (LCMS 2), two lasers, are mounted in the rear of the vehicle.
- The LCMS 2 collects 3D images of the pavement allowing us to detect cracking, rutting, texture, potholes, shoving, raveling and roughness. Pavement distresses can be measured with 1mm resolution.
- An operator and a driver are needed to conduct video log testing.



TESTING REQUESTS

Testing Request Forms can be accessed using the RITU intranet website:

https://dot.state.pa.us/penndot/Bureaus/Intranet/BOMOintra.nsf/infoRMRIhome?OpenForm

Requested By:					Title:			District/f	District/Bureau:				
Phone Number: Fax Number:			Address: Address Line 1: (Required if testing results are to be city. State, Zip					b b R					
Type of Test	County /State	SR (s)	From Segment	From Offset	If Non State Road, Please specify a	To	To Offset	If Non State Road, Please specify an	Dir.	Test Lane (s)	Total Test		
		-		-	starting location			enuing location	-		white a		
		1					-		•1		-		
ك.	-								•				
	1								-1				
		1	2						-	-			
	-	· · · ·	100 million						+1	-			
<u>لد</u>	1								-1	-			
-	ات.	1							1		1		
	-								*1	-			
*	100								100		-		
Il testing requi	ests of <u>n</u> e emailed	n state faxed	owned ro.	ads mus with this	t include a map of th testing request for	ve arealis) I n.	o be tes	ted.					
All testing requ the map can be S For Skid K I For Skid D O Further N <u>Pspenno</u> L <u>Data/Ski</u> Y	ests of <u>nx</u> e emailed testing, p Testing p Informat iot share DyPerinD	in state l, faxed ilease s ilease s ilease s ilease s ilease s ilease s ilease s	elect a reas elect test ti PennDOT u of Mainto Penicy.pdf	ads mus with this on for th re type: s skid/f enance a	L include a map of the testing request for the request: C Blank of riction pavement p and Operations/Rea	relicies ca	n be fou	•] •] nd at the following t Division/Roadway	glocatio	n: y & Testing(s	hared		

Curr										
Current Date.					District/Bureau:		1			
Reque	sted B	y:			Title:					
hone	Numb	er:			А	ddress:				
Fax Number:					(F	equired if sting results				
Email:				a	e to be alledi					
lease f	fill out a	separate f	form for eac	h individual Si	t or pavement	section to be	tested.			
f a <u>div</u> ellow s	ided SR section f	needs to h or the Sou	have testing ith/West or	done in each odd segment	direction, use	the blue sect	ion below f	or the North/	East or even se	egments and the
			-	Test L	ocation			in the second	Total	Design
0	ounty	58	Seament	Offset	Segment	Offset	Elt	to Test	Test Miles	Field View Date
-	-1		segments				-1	-1		
Int	Odd Segm	ents Onlart					-			
Surface		Joint	Base			SubBa	se	SubGrade		
	Type D		Depth (In)	Spacing (ft)	Type Depth		h (in)	Туре	Depth (in)	туре
_		_			Turneral	aution Door	i land			
C	Basin T	esting	*Note: Bas	in Testing is for I	Bituminous Pave	ements only, at	a fixed test i	interval, minim	um 10 test poin	ts per pavement
F A E C	Basin T or Basin T idjacent L basting P Load T or Joint T	esting Testing on anes be sta averment T) ransfer Testing on F	*Note: Bas section spa Flexible or C ggered, (Us gpe: C Fle C Before Rigid Pavent	in Testing is for) cing not to exce omposite Paven laily 'yis']? xible Com and After Joint ants;	Ettuminous Paw ed 250ft. If a ck rents, (* if Pub 2 iposite Other, please	ements only, a ser test interv 42 criteria is m specify	t a fixed test i al is required let), in both d	interval, minim please specify frections, shou	um 10 test poin : id lest locations	ts per payement
F A R	Basin T diacent b existing P Load T or Joint T a) Selec	esting Testing on anes be sta avement Ty ransfer Testing on F t Pavemen	*Note: Bas section spa Flexible or C ggered, (Us, ype: C File C Before: Ngid Pavenw t Joint Test N	In Testing is for) cing not to exce omposite Paven ially "yes")? xible Com and After Joint ants: hterval: Every	Bituminous Paw ed 250ft, if a ck rents, (* if Pub 2 posite Other, please	ements only, a oser test interv 42 criteria is m specify C 2nd Join	t a fixed test i al is required et), in both d	ntewal, minim please specify inections, shot	ium 10 test poin r Ind lest locations	ts per pavement
F a E F	Basin T djacent L Existing Pr Load Ti for Joint T a) Selec b) Selec	esting Testing on anes be sta averment Ty ransfer Testing on F t Pavernen t Pavernen tt Patch Joie	*Note: Bas section spa Flexible or C ggered. (Us. ype: C Fle C Before Rigid Pavent t Joint Test Inten	In Testing is for 1 cing not to exce omposite Paven iaily "yes")? xible Com and After Joint arts: nterval: Every rai: Every	Bituminous Paw ed 250ft. If a ck nents, (* If Pub 2 posite Dther, please C 1st Joint. C 1st Joint	ements only, al oser test interv 42 criteria is m specify C 2nd Join C 2nd Join	t a fixed test i al is required et), in both d t C 3r t C 3r	nterval, minim please specify inections, shou d Joint Or d Joint Or	um 10 test poin d lest locations her Please Spec	ts per pavement s m •) Ny:
F A B A B A B A B A B A B A B A B A B A	Basin T ior Basin i idjacent L Existing Pri Load Tr for Joint T a) Selec bi Selec Void Do	esting Testing on a arres be sta avernent Ty ransfer Testing on P t Pavement t Pavement tt Patch Join etection	*Note: Bas section spa Flexible or C ggered. (Us ype: C Fle C Before Nigid Pavenu t Joint Test Inten C Before	In Testing is for 1 cing not to exce omposite Paven tally "yes")? xitble Com and After Joint interval: Every rai: Every and After Joint	Bituminous Paw ed 250ft. If a ck ments, (* if Pub 2 ipposite Detier, please C 1st Joint Other, please	ements only, al seer test interve 42 criteria is m specify C 2nd Join C 2nd Join specify	t a fixed test i al is required etj, in both d t C ar t C ar	nterval, minim please specify inections, shot d Joint Of d Joint Of	um 10 test poin : Id lest locations her Please Spec	ts per pavement sim •) Ify:
F F F Icase se roject (Basin T idjacent i kijacent i kisting Pi Load Ti Load Ti for Joint T a) Selec Void Di Void Di charge Ni	esting Testing on a averse to sta aversent Ty ransfer esting on P f Pavemen it Patch Join estection r you would umbers: p	*Note: Bas section spa Flexible or C gggered, (Us gggered, (Us Fle Flexible Before 1 Alont Test In nt Test Inten Estiment flike to rece tec. CCtr	In Testing is for 1 cing not to exce omposite Paven ially "yes")? xible Com and After Joint arts: nterval: Every and After Joint ive the testing re	Bituminous Paw ed 250ft. If a ck rents, (* If Pub 2 iposite Dther, please C 1st Joint Other, please suits: E ar Receiver WB	ements only, al oser test interv 42 criteria is m specify C 2nd Join Specify all Per S Element	t a flored test i lis required et), in both d t C 3r t C 3r t C 3r	nterval, minim please specify Inections, shop d Joint Or d Joint Or d Drive	um 10 test poin c id test locations her Please Spec her Please Spec inter Office Ma Fund	ts per pavement
F F F Iease se roject (idditio	Basin T idjacent L idjacent L ixisting P: Load Ti or Joint T a) Selec b) Selec Void Di elect how Charge Ni mal Com	esting Testing on in anes be sta avernent Ty ransfer Festing on P t Pavemen t Pavemen st Patch Join etection r you would umbers: R ments:	*Note: Bas section spa Flexible or C ggered, (Us ggered, (Us ggered, (Us Fle C Before igit Pavent r Joint Test In the Test Inten C Before flike to rece lec. CCtr	in Testing is for 1 cing not to exce omposite Paven ally "yis?? xible Com and After soint arits: interval: Every val: Every and After Joint ive the testing re	ed 250ft, if a ck ments, (* If Pub 2 possite Detrer, please C 1st Joint Other, please suits: E an Beceiver WB	ements only, si oser test interv 42 criteria is m C 2nd Join C 2nd Join specify all Per 5 Element	t C 3r t C 3r t C 3r t C 3r	nterval, minimu please specify inections, shou in Joint Or d Joint Or d Drive	um 10 test poin r Int lest locations her Please Spec her Please Spec Inter Office Ma Fund	its per pavement
F a B B B B B B B B B B B B B B B B B B	Basin T or Basin T dijacent L existing Pri Load Tr a) Selec b) Selec Void Di elect how Charge Ni mal Com	esting Testing on i arres be sta avement Ty consfer Pavement t Patch Join exection r you would umbers: R ments:	*Note: Bas section spa Feedble or C ggrend, (Us yre: C File C Before Hight Pavement A Joint Test Intern C Before d like to rece leec. CCtr	In Testing is for 1 cing not to exce omposite Paven and After Joint and After Joint After Joint Paven and After Joint Ive the testing in	Stuminous Paw ed 250H, if a cl ments, (*) (F Ve 2 positie Dether, please C hst.Joint Other, please suits: E en Receiver WB	ements only, ai seer test interv 42 ordenia is m 2 and Join 2 and Join specify: asil Pets 5 Element	t C 3r t C 3r t C 3r t C 3r t G	nterval, minim please specify inections. shou d Joint Of d Joint Of d Drive	um 10 test poin c Inter Please Spect her Please Spect inter Office Ma Fund	its per pavement
F a c c c c c c c c c c c c c c c c c c	Basin T for Sasin L diacent L soluting Pr Load Ti for Joint T a) Selec b) Selec Void Du elect how Charge Ni mal Com	esting Testing on a new be sta averment T ranffer esting on P t Pavemen tt Patch Joie etection ryou would umbers: g ments: sts To:	*Note: Bas section spa Flexible or C gogened. (Us) gogened. (Us) (C Before Bigid Paveme t Joint Test In the Test Intern C Before d like to rece lec. CCtr	In Testing is for 1 cling not to exec on possile Faverage ally "yes")? Table Com- and After Joine we the testing in y E. Reed, Chile uneau of Maint O? Elimetron A: mail: Tyreed	attuninous Paw ed 250h; if a cl ients, if i Pub 2 posite Differ, please C 1st Joint Other, please suits: E en Receiver WB1 (ROMO, Road enance & Ope we Harrisburg spagov Ph	ements only, a ser test interv 42 criteria is m specify C and Jain C and Jain Specify all Pet 5 Element way Invention rations - BOA PA 1710 PA 1710 PA 17170 78	t C sr t C sr t C sr t C sr t C sr t C sr t	nterval, minem please specify inections, shoo d Joint Or d Joint Or d Joint Or d Drive T	um 10 test point in the focusions her Please Specher Please Speche	is per povement

FUGRO

- Fugro Data collection
 - Collect all PennDOT miles almost 40,000 segment miles
 - Collect Business Plan Networks 1 (interstate) and 2 (National Highway System - NHS) Annually
 - Collect Business Plan Networks 3 (Non-NHS >2000 ADT) and 4 (Non-NHS <2000 ADT) Every other year
 - Collect IRI, OPI, and 18 other pavement Distresses
 - Report to FHWA though HPMS (Highway Performance Monitoring System)







ROADWAY MANAGEMENT SYSTEM

- RMS is the system of record for our roadways;
 - Maintains an inventory of the roadway features, conditions, and characteristics
 - Provides decision-makers with the information necessary for funding, business planning, project design, maintenance programming, and information for the annual allocation of maintenance funding
 - Data stored and managed in RMS includes;
 - Geometry information
 - Traffic information
 - Pavement and shoulder history
 - Maintenance history
 - Municipal and legislative boundaries
 - Intersections

13201w(C01 4 102303			0.48
	1 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4		
	RNSRN771 ROADMAY NANAGEME	ENT ENFORMATION SYSTEM 25/13/2016 11:04:29	
	LTERR: HELMHKI TREHIMER	I DEELNE	
		SEGMENT	
	COUNTY ND. COUNTY NAME SR F	RDN TO DIR YEAR GROUP	
	BITUHINOUS	CONCRETE	
	B1 - ROUTINE WAINTENANCE	C1 - ROUTINE MAINTENANCE	
	82 - SEAL DDAT	C2 PRESERVATION DPR	
	E3 MINDR REHABILITATION	C3 - PRESERVATION - DPR & DVERLAY	
	E4 - MAJDR REHABILITATION	C4 - RECONSTRUCT	
	B5 - RECONSTRUCT		
	DAPHYED		
	12 SUBPTING	R2 - C R C RETCHING	
	U3 - RESTABLIZATION	R3 - NAJOR REPORT LITATION	
	ACTION I IDEGHIJPORSK)		
	NESSAGES:		
	NA a	06/006	
	-		
			100 XI 11 11
a a lalistis			LW
			-14091

- Roadside features
- Structure locations
- Railroad crossings information
- Pavement testing
- Condition survey information (including guiderail and drainage)
- Posting/bonding information

RMS STRAIGHT LINE DIAGRAM

- One of the most important aspects of RMS is having a viewable representation of a state road (SR).
- This is accomplished with a graphical diagram called a straight-line diagram (SLD).
- PennDOT produces electronic versions of the SLD for every state road, in every county, annually.





ROADWAY MANAGEMENT SYSTEM

Many other PennDOT computer systems depend on data from RMS





D196 REPORTS

- State-wide pavement data collected by Fugro
- Internally facing information
- D196 comes in a variety of reports;
 - Each business plan network
 - International Roughness Index (IRI) Median and Miles reports
 - Overall Pavement Index (OPI) Median and Miles reports





PAVEMENT HISTORY

- Pavement History is the documented layers of pavement entered into RMS by the Districts
- Both internally and externally facing
- Link to Pavement History: <u>https://gis.penndot.gov/PavementHistory/</u>

					ft-lome Tutorial Abou
tion: 22 - DAUPHIN +	0022 - WILLIAM PE * 0010 - WILLIAM	A PE 🔹 Show Street Names VideoLog Hide Map C	Current Location		
	PAVEMENT HISTORY	s Segments	Scale	Map Satellite	OSM THE
	22 - DAU	JPHIN, 0022, WILLIAM PENN HW, Segment: 0010			(17) Liverpool
		Switch Sildes			
				Millerstown	Millersburg
			08 HS		Mt Patrick
			037 —		
		0010			(II) Fishery
	8			Wila Newport Bailey	
	(803			(01)	Halifax
				(34) (49)	22) 15
					(III)
r(fl)				Total - 1673(ft)	Inglencok (25)
	500	000t			Duncannon (73)
				Mecks Corner	Singersville
tion Status				(34) Delivitie	Dauphin
wement width					Marysville
Wonnesst Widdit				nans Dale	
ent History Layer Type Code	e				Summerdale
and the second	- Annihuman A				Enola
MA WRG,76-22,12.5MM,E / Dep	th: 2 (in.) / Year: 2016			(94)	Vertzville 946 Harrisbe
MA BNDR, 76-22, 19MM / Depth	. 2.5 (in.) / Year: 2016				Good Hope



PAVEMENT HISTORY

Total pavement width

24

Pavement History Layer Type Code

2017

SPAV,WMA WRG,64-22,12.5MM,E / Depth: 2 (in.) / Year: 2017

MILLING (AVERAGE DEPTH) / Depth: -2 (in.) / Year: 2017

2012

SPAV,HMA WRG,64-22, 9.5M..

MILLING (AVERAGE DEPTH ...

2010

SURFACE TREATMENT - RALUMAC / Depth: .63 (in.) / Year: 2010

1998

ASPHLT MX HMA WEARING, 19 MM / Depth: 1.5 (in.) / Year: 1998

HEAVY DUTY BINDER COURSE ID2 / Depth: 2 (in.) / Year: 1998

SCRATCH BIT WEAR COURSE ID-2 / Depth: .62 (in.) / Year: 1998

CONC PVMT RESTORATION (CPR) / Depth: 0 (in.) / Year: 1998

1972

RCCP 46.5 (ft.) JNT SPACING/DOWEL / Depth: 10 (in.) / Year: 1972

- Record of existing pavement layers, those which have been reconstructed are no longer listed
- Each line includes some or all of the following information:
 - PG, Aggregate size, SRL, Material type, depth, milling depth, or time of placement
- Scale at the top denotes where the material was placed or removed within the segment



VIDEOLOG

- VideoLog is the term used to describe the automated collection of pavement conditions and roadway imagery.
- VideoLog data is collected on all state-owned asphalt and jointed concrete pavements by a vehicle called a VideoLog Van or Video Van.
 - Data collected is a series of individual pictures set in intervals that are sequenced together
- VideoLog is both internally and externally facing
- Link to VideoLog: <u>https://gis.penndot.gov/videolog/</u>



VIDEOLOG





VIDEOLOG BENEFITS

- There are two key benefits gained with VideoLogging;
 - Safety:
 - Conducting manual pavement surveys can present hazards for PennDOT personnel because the process involves traveling on the roadway shoulder at slow speeds.
 VideoLogging replaces the need for frequent manual survey, so it is much safer.
 - Efficiency:
 - VideoLogging provides panoramic images for personnel to view, instead of having to physically travel to a location to view pavement conditions.

ect Area of Interest								
COLINTY	ROUTE SEG	INTERSECTION STREET N	17102 AME ZIP CODE	MUNICIPALITY	BRIDGE ID	MPM5 PROJECT ID	STREET ADDRESS	LAT/LONG
DUTE# - Select from the optic	ons below then click Go!							
County	<select county=""></select>							





VIDEOLOG



Historical Data available through "Show Historical VideoLog" check box





Q

PDIF

- Penndot Data Integration Facility (PDIF) Internal Facing
- Applications: Road Management for BOMO (ROAD)



- Reports:
 - Roadway Management
 - Pavement History
 - Posted and Bonded
 - STAMPP





PENNDOT ONE MAP



PAMS

- Pavement Asset Management System (PAMS) is an asset management solution that assists with strategic planning with maintenance operations and capital investment decision making
- Project optimization based on funding
- Future prediction of deterioration and benefits from proposed projects
- Bring together data from multiple systems for analysis and reporting





PAVEMENT ASSET MANAGEMENT SYSTEM

- PAMS connects to other PennDOT systems (legacy and updated systems) to ensure smart project recommendations
 - Planning information comes from MPMS
 - Historical information and past treatments and condition data from RMS
 - Maintenance from SAP
 - Construction projects and costs from ECMS
 - Mapping from GIS

V000 2024 2024 2028 2028	 ************************************	T Name T T T	7 Fram 0.956 0.000	7 T 4.635	T Longili 3.679	TREATING	¥ 007
2024 2024 2028 2028	01-0094-1) 01-0194-8 02:0009-1)	1 3 5	0.956	4.635	3.679	LEVEL_RESURFACE	\$4,000,020.71
2024 2028 2028	01-0194-8 02:0005-N	3.	0.000			a second and the second se	
2028 2028	62 0005 N	3		1.950	1.950	LEVEL_RESURFACE	\$2,023,960.22
2028			2:749	3,148	0.399	RECONSTRUCTION	\$1,355,465.51
	02:0008-5	10	8.634	8.467	1.033	RECONSTRUCTION	\$9,668,123,01
2028	02-0008-5	9	2,752	3.148	0.396	RECONSTRUCTION	\$1,346,266.52
2023	02-0019-N	12	0.000	1.229	1.229	RECONSTRUCTION	\$5,222,732.18
2025	02-0019-10	.14	2.323	4,622	2.299	LEVEL_RESURFACE	\$3,579,295.81
2028	02-0018-M	15	5.602	7.005	1.404	LEVEL_RESURVACE	\$2,252,115,74
2023	02-0018-5	18	0.000	1.852	1.852	RECONSTRUCTION	57,870,219,59
2023	02-0019-5	:19	1.859	2.312	0.453	RECONSTRUCTION	51,848,056,77
2023	02-0019-5	21	10.807	10,983	0,176	LEVEL_RESURFACE	\$199.282.24
2023	02-0019-9	22	10.987	11,495	0.508	LEVEL_RESURFACE	3375 201.00
2025	0/2-007/8-Jy	27	5.377	7.097	0.720	MILL LEVEL RESURFACE	\$1.004,098.87
2023	02-0028-N	25	19,865	24,087	4,222	RECONSTRUCTION	517.224.052.29
2023	02:0028-5		0.474	10,707	0.233	RECONSTRUCTION	\$1,126,541/16



TRANSPORTATION ASSET MANAGEMENT PLAN (TAMP)

- MAP-21 and the FAST Act require each state department of transportation to develop and implement a risk-based asset management plan in accordance with 23 U.S.C. 119
- The intent is to encourage states to achieve and sustain a state of good repair over the life cycle
 of transportation assets—regardless of ownership—and to preserve or improve the condition of
 the NHS.
- The Pennsylvania Transportation Asset Management Plan (TAMP) 2019:
- A recent TAMP submission was made the end of 2022, FHWA has 90 to review and approve the submission
 - Establishes targets for pavement and bridge condition
 - Summarizes Pennsylvania's inventory of pavement and bridge assets by structure type, class, owner, and condition
 - Forecasts asset condition by year for at least a 12-year planning horizon at current funding levels
 - Outlines PennDOT's asset management practices, which are integrated into long-range planning, project programming, financial planning, and risk assessment processes

PTAMS MOVING FORWARD



QUESTIONS?

Halley Cole P.E.

Chief Pavement Testing and Asset Management halcole@pa.gov

